

# Field Data Collection

Purpose Built for  
Corrosion Prevention  
and Control



Part of the [PCS Field Integration](#) suite of hardware and software solutions, PCS Field Data Collector enables you to perform annual, periodic, DCVG, and close interval surveys, and validate inspection data in real time. Available for Android devices on Google Play, Allegro AX Field Data PC via the American Innovations Support Site, and Apple iOS devices on the App Store.

**Visualize** survey routes with maps, and quickly identify and troubleshoot problems. Continuous improvements make it easy to stay ahead of survey demands.

**Integrate** seamlessly with the DVM2130 or DVM1110 digital voltmeters, built specifically for the cathodic protection industry.

**Sync** surveys [wirelessly](#) using PCS Wireless Sync, American Innovations' SOC2-Compliant cloud integration technology.

# PCS FIELD DATA COLLECTOR REQUIREMENTS

## Device and Software Requirements

- ✓ [Allegro AX Field Data PC](#) with DVM1110 digital voltmeter
- ✓ [Mesa 3 Rugged Tablet](#) with DVM2130 digital voltmeter
- ✓ Apple devices: iOS version 15 or above for certain iPads. Optimized for use with the DVM2130 digital voltmeter.
- ✓ PCS 2.2 or newer and PCS Survey Manager, if using PCS Wireless Sync
- ✓ PCS 1.14 or newer, if using drag-and-drop on iOS for annual/periodic surveys or USB with Android and Allegro devices.

## FAQs

### Where can I find more information?

Contact customer support via phone (800-229-3404) or email ([support@aiworldwide.com](mailto:support@aiworldwide.com)) or your sales representative or the American Innovations Support Site ([support.aiworldwide.com](http://support.aiworldwide.com)).

### Where can I download new versions of the PCS Field Data Collector software?

- ✓ Mesa 3 Rugged Tablet users: download from the [Google Play Store](#)
- ✓ Allegro AX Field Data PC users: download from the [American Innovations Support Site](#)
- ✓ Apple device users: download from the [Apple App Store](#)

### Do I need an internet connection to use the PCS Field Data Collector software?

An internet connection is needed for initial login to the software, but typical use of the software does not require an internet connection.

### How frequently do I need to reauthenticate my login credentials for the PCS Field Data Collector software?

After logging in initially, users need to reauthenticate every 90 days with an active internet connection.

**NOTES.** The DVM2130 and DVM1110 digital voltmeters have an IP67 rating for moisture and dust protection, operating temperature range of -4° F to 122° F (-20° C to 50° C), and storage temperature range of -22° F to 158° F (-30° C to 70° C). Refer to your host device documentation for additional environmental specifications/ratings.



**Visualize. Integrate. Sync.**



**LEARN MORE:** [aiworldwide.com/pcsfdc](http://aiworldwide.com/pcsfdc)

aiworldwide.com • 800-229-3404 • [info@aiworldwide.com](mailto:info@aiworldwide.com)  
12211 Technology Blvd. Austin, TX 78727